

# volzFix V4023 PV1



volzFix V4023 PV1 is a double-sided adhesive tape consisting of a cotton-cloth backing and a transparent, differentiated strong / weak, hot-melt rubber adhesive. The product is very suitable as a trade show installation tape. The high mass application allows bonding on rough and textured surfaces and shows a high initial tack.

## **Nominal Values**

Backing	Cotton Cloth
Adhesive Type	Synthetic Rubber, Clear, different adhesion on each side, open side: removable, closed side: permanent sticking
Total Thickness	0,340 mm
Color	Clear (00)
Liner	65 g, Yellow, siliconized Paper
Length	5 m, 25 m, 50 m, 500 m, 1000 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 December 2021



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com









ra UL-Zertfidærter Konfektonår UL-cettfied Re-packager



## volzFix V4023 PV1



### **Applications**

• Perfect Exhibition tape

### **Benefits**

- Hand tearable
- Flexible carrier
- Excellent tack on the open side
- Residue-free on the closed side

#### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.09.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com









