volzFix V4023



volzFix V4023 is a double-sided adhesive tape consisting of a cotton-cloth backing and a transparent, differentiated strong / weak, hot-melt rubber adhesive. The product is very suitable as a trade show installation tape. The high mass application allows bonding on rough and textured surfaces and shows a high initial tack.

Nominal Values

Backing	Cotton Cloth
Adhesive Type	Synthetic Rubber, plasticizer free, Clear
Total Thickness	0,340 mm
Color	Clear (00)
Liner	65 g, brown, bi-siliconized, Paper
Adhesion to Steel	O: 12,50 N/25 mm, G: 17,50 N/25 mm
Tensile Strength	74,50 N/25 mm
Elongation at Break	< 3,7%
Shear Strength	O: 1 h, A: 3 h
Rolling Ball Tack	O: 2 cm, G: < 1 cm
Temperature Resistance	-20°C to +65°C
Length	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	26 November 2019

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V4023



Applications

- Perfect Exhibition tape

Benefits

- Hand tearable
- Flexible carrier
- Excellent tack on the open side
- Residue-free on the closed side

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com