

## volzFix V4023



volzFix V4023 is a double-sided adhesive tape consisting of a cotton-cloth backing and a transparent, differentiated strong / weak, hot-melt rubber adhesive. The product is very suitable as a trade show installation tape. The high mass application allows bonding on rough and textured surfaces and shows a high initial tack.

## Nominal Values

<b>Backing</b>	Cotton Cloth
<b>Adhesive Type</b>	Synthetic Rubber, plasticizer free, Clear
<b>Total Thickness</b>	0,340 mm
<b>Color</b>	Clear (00)
<b>Liner</b>	65 g, brown, bi-siliconized, Paper
<b>Adhesion to Steel</b>	O: 12,50 N/25 mm, G: 17,50 N/25 mm
<b>Tensile Strength</b>	74,50 N/25 mm
<b>Elongation at Break</b>	< 3,7%
<b>Shear Strength</b>	O: 1 h, A: 3 h
<b>Rolling Ball Tack</b>	O: 2 cm, G: < 1 cm
<b>Temperature Resistance</b>	-20°C to +65°C
<b>Length</b>	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	26 November 2019

## volzFix V4023



### Applications

- Perfect Exhibition tape

### Benefits

- Hand tearable
- Flexible carrier
- Excellent tack on the open side
- Residue-free on the closed side

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.09.2025