

## **Technical Product Data Sheet**

## volzFix V4032 PV1



volzFix V4032 PV1 is a double-sided, self-adhesive tape with a polyester-cloth carrier and a white, hot-melt, syntheticrubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces.

#### **Nominal Values**

PFT Cloth **Backing** 

**Adhesive Type** Synthetic Rubber

**Total Thickness** 0,185 mm

> Color White (08)

Liner 65 g, yellow, siliconized Paper

Adhesion to Steel (N/25mm) > 27,50 N/25 mm

> **Tensile Strength** 85.00 N/25 mm

**Elongation at Break** 18%

> **Shear Strength** > 5 h

**Rolling Ball Tack** □ 2 cm

**Temperature Resistance** -10°C to +50°C

> Length 50 m, 100 m, 1000 m, 1600 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 05 March 2021





Phone: +49 (0)7664 50500-0 +49 (0)7664 50500-50

info@volztapes.com www.volztapes.com



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











# **Technical Product Data Sheet**

## volzFix V4032 PV1



### **Applications**

- Carpet laying and trade show tape (permanent or temporary)
- Bonding of foams, metal foils, cardboards, posters or other materials
- Bonding for standard industrial applications
- Strong adhesion
- Very conformabe on different surfaces
- Hand tearable
- Flexible carrier
- Thick adhesive mass

### **Benefits**

- Good adhesion
- Good conformability onto different surfaces Hand tearable
- Flexible carrier
- Thick adhesive mass

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.04.2024



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.











DE-79227 Schallstadt