

volzFix V4032 PV1



volzFix V4032 PV1 is a double-sided, self-adhesive tape with a polyester-cloth carrier and a white, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces.

Nominal Values

Manufacturer	VOLZ®
Backing	PET Cloth
Adhesive Type	Synthetic Rubber
Total Thickness	0,185 mm
Color	White (08)
Liner	65 g, yellow, siliconized Paper
Adhesion to Steel	> 27,50 N/25 mm
Tensile Strength	85,00 N/25 mm
Elongation at Break	18%
Shear Strength	> 5 h
Rolling Ball Tack	< 2 cm
Temperature Resistance	-10°C to +50°C
Length	50 m, 100 m, 1000 m, 1600 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	05 March 2021

volzFix V4032 PV1



Applications

- Carpet laying and trade show tape (permanent or temporary)
- Bonding of foams, metal foils, cardboards, posters or other materials
- Bonding for standard industrial applications
- Strong adhesion
- Very conformable on different surfaces
- Hand tearable
- Flexible carrier
- Thick adhesive mass

Benefits

- Good adhesion
- Good conformability onto different surfaces Hand tearable
- Flexible carrier
- Thick adhesive mass

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024