

volzFix V4032



volzFix V4032 is a double-sided, self-adhesive tape with a PET Cloth carrier and a white, hot-melt synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces.

Nominal Values

| | |
|-------------------------------|---|
| Backing | PET Cloth |
| Adhesive Type | Synthetic Rubber |
| Total Thickness | 0,185 mm |
| Color | White (08) |
| Liner | 65 g, brown, siliconized Paper |
| Adhesion to Steel | > 27,50 N/25 mm |
| Tensile Strength | 85,00 N/25 mm |
| Elongation at Break | 18% |
| Shear Strength | > 5 h |
| Rolling Ball Tack | < 2 cm |
| Temperature Resistance | -10°C to +50°C |
| Length | 50 m, 100 m, 1000 m, 1600 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 14 April 2020 |

volzFix V4032



Applications

- Carpet laying tape for exhibitions
- Bonding of foils, cardboards, posters and more
- Bonding for standard industrial applications

Benefits

- Good adhesion
- Good conformability onto different surfaces Hand tearable
- Flexible carrier
- Thick adhesive mass

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.07.2026