

Technical Product Data Sheet

volzFix V4032



volzFix V4032 is a double-sided, self-adhesive tape with a PET Cloth carrier and a white, hot-melt synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces.

Nominal Values

Backing PET Cloth

Adhesive Type | Synthetic Rubber

Total Thickness 0,185 mm

Color White (08)

Liner 65 g, brown, siliconized Paper

Adhesion to Steel > 27,50 N/25 mm

Tensile Strength 85,00 N/25 mm

Elongation at Break 18%

Shear Strength > 5 h

Rolling Ball Tack < 2 cm

Length 50 m, 100 m, 1000 m, 1600 m, other lengths upon request

Width 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 14 April 2020















DE-79227 Schallstadt



Technical Product Data Sheet

volzFix V4032



Applications

- Carpet laying tape for exhibitions
- Bonding of foils, cardboards, posters and more
- Bonding for standard industrial applications

Benefits

- Good adhesion
- Good conformability onto different surfaces Hand tearable
- Flexible carrier
- Thick adhesive mass

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.08.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of







