

volzFix V4033 PV1



volzFix V4033 PV1 is a double-sided adhesive tape with polyester-cloth carrier. The tape is suitable for permanent or temporary carpet laying preparation at exhibitions and domestic applications. Also for miscellaneous industrial splicing and mounting applications.

Nominal Values

Backing	PET Cloth
Adhesive Type	Synthetic Rubber, White
Total Thickness	0,165 mm
Color	White (08)
Liner	65 g, yellow, bi-siliconized, Paper
Adhesion to Steel	> 20,00 N/25 mm
Tensile Strength	85,00 N/25 mm
Elongation at Break	18%
Shear Strength	> 5 h
Rolling Ball Tack	< 4 cm
Temperature Resistance	-10°C to +60°C
Length	25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	05 March 2021

volzFix V4033 PV1



Applications

- Permanent or temporary carpet laying preparation
- Miscellaneous industrial splicing and mounting

Benefits

- Excellent Adhesion to All Surfaces
- Good Adaptability on Different Surfaces and Shapes
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.04.2025