

Technical Product Data Sheet

volzFix V4033



volzFix V4033 is a double-sided adhesive tape with PET Cloth carrier. The tape is suitable for permanent or temporary carpet laying preparation at exhibitions and domestic applications. Also for miscellaneous industrial splicing and mounting applications.

Nominal Values

PFT Cloth **Backing**

Adhesive Type Synthetic Rubber, White

Total Thickness 0,165 mm

> Color White (08)

Liner 65 g, brown, bi-siliconized, Paper

Adhesion to Steel > 20,00 N/25 mm

Tensile Strength 85.00 N/25 mm

Elongation at Break 18%

> **Shear Strength** > 5 h

Rolling Ball Tack < 4 cm

Temperature Resistance -10°C to +60°C

> Length 25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 26 November 2019





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











Technical Product Data Sheet

volzFix V4033



Applications

- Permanent or temporary carpet laying preparation
- Miscellaneous industrial splicing and mounting

Benefits

- Excellent Adhesion to All Surfaces
- Good Adaptability on Different Surfaces and Shapes
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 26.11.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of







