

Technical Product Data Sheet

volzFix V4039 PV1



volzFix V4039 PV1 is a double-sided, self-adhesive tape produced with a cloth carrier and a thick, tacky, solvent free, synthetic rubber based adhesive system. The product is a all-round good mounting tape, perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all rough and smooth surfaces. The product has a very high tack.

Nominal Values

Backing Cotton Cloth

Adhesive Type Synthetic Rubber, solvent free, Clear

Total Thickness 0,200 mm

Color Clear (00)

Liner 80 g, yellow, bi-siliconized, Paper

Adhesion to Steel 36,25 N/25 mm (kurzfristig), 60,00 N/25 mm (langfristig – nach 14 Tagen)

Tensile Strength 87,50 N/25 mm

Elongation at Break 20%

Temperature Resistance +60°C (short-term), +40°C (long-term)

Length 25 m, 50 m, 100 m, 500m, other lengths upon request


Width 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1400

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 21 February 2024















DE-79227 Schallstadt



Technical Product Data Sheet

volzFix V4039 PV1



Applications

- Carpet laying tape for exhibitions
- Bonding of foils, cardboard, posters and more
- Bonding for standard industrial applications

Benefits


- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Flexible carrier
- Thick adhesive mass
- · Good moisture resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 13.12.2025













DE-79227 Schallstadt