

# **Technical Product Data Sheet**

## volzFix V4039 PV1



volzFix V4039 PV1 is a double-sided, self-adhesive tape produced with a cloth carrier and a thick, tacky, solvent free, synthetic rubber based adhesive system. The product is a all-round good mounting tape, perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all rough and smooth surfaces. The product has a very high tack.

## **Nominal Values**

**Backing** Cotton Cloth

**Adhesive Type** Synthetic Rubber, solvent free, Clear

**Total Thickness** 0,200 mm

Color Clear (00)

**Liner** 80 g, yellow, bi-siliconized, Paper

**Adhesion to Steel** 36,25 N/25 mm (kurzfristig), 60,00 N/25 mm (langfristig – nach 14 Tagen)

**Tensile Strength** 87,50 N/25 mm

**Elongation at Break** 20%

**Temperature Resistance** +60°C (short-term), +40°C (long-term)

**Length** 25 m, 50 m, 100 m, 500m, other lengths upon request


**Width** 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1400

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 21 February 2024















DE-79227 Schallstadt



# **Technical Product Data Sheet**

# volzFix V4039 PV1



### **Applications**

- Carpet laying tape for exhibitions
- Bonding of foils, cardboard, posters and more
- Bonding for standard industrial applications

#### **Benefits**

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Flexible carrier
- Thick adhesive mass
- · Good moisture resistance

#### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.08.2025













DE-79227 Schallstadt