

Technical Product Data Sheet

volzFix V4040 PV1



volzFix V4040 PV1 is a double-sided, self-adhesive tape with a cotton-cloth carrier and a clear, hot-mel,t plasticizerfree, synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces. The product has also a very high tack.

Nominal Values

Cotton Cloth **Backing**

Adhesive Type Synthetic Rubber, plasticizer free, Clear

Total Thickness 0,260 mm

> Color Clear (00)

Liner 0,060 mm, 65 g, brown, bi-siliconized, Paper

Adhesion to Steel > 32,00 N/25 mm

Tensile Strength > 62,00 N/25 mm

Elongation at Break < 6%

> **Shear Strength** > 14 h

Rolling Ball Tack < 3 cm

Temperature Resistance -20°C to +65°C

> Length 5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 18 March 2022













DE-79227 Schallstadt



Technical Product Data Sheet

volzFix V4040 PV1



Applications

- Carpet laying tape for exhibitions, permanent or temporary
- Bonding of foils, cardboards, posters and more
- Bonding for standard industrial applications

Benefits


- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier
- Thick adhesive mass

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.12.2025













DE-79227 Schallstadt