

volzFix V4040 PV1



volzFix V4040 PV1 is a double-sided, self-adhesive tape with a cotton-cloth carrier and a clear, hot-mel,t plasticizerfree, synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces. The product has also a very high tack.

Nominal Values

Backing	Cotton Cloth
Adhesive Type	Synthetic Rubber, plasticizer free, Clear
Total Thickness	0,260 mm
Color	Clear (00)
Liner	0,060 mm, 65 g, brown, bi-siliconized, Paper
Adhesion to Steel	> 32,00 N/25 mm
Tensile Strength	> 62,00 N/25 mm
Elongation at Break	< 6%
Shear Strength	> 14 h
Rolling Ball Tack	< 3 cm
Temperature Resistance	-20°C to +65°C
Length	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	18 March 2022



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com







fera





volzFix V4040 PV1



Applications

- Carpet laying tape for exhibitions, permanent or temporary
- Bonding of foils, cardboards, posters and more
- Bonding for standard industrial applications

Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier
- Thick adhesive mass

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 31.07.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com +49 (0)7664 50500-50 www.volztapes.com









