volzFix V4100



volzFix V4100 is a double-sided, self-adhesive tape with a white, cast PP carrier and a clear, synthetic-rubber adhesive. The product is perfect for carpet laying or industrial bonding of different surfaces. The thick adhesive mass makes the tape suitable for all even and uneven surfaces. The product also has a very high tack.

Nominal Values

Backing	White, cast, PP Film
Adhesive Type	Synthetic Rubber
Total Thickness	0,185 mm
Color	White (08)
Liner	65 g, brown, bi-siliconized, Paper
Adhesion to Steel	> 29,00 N/25 mm
Tensile Strength	> 62,00 N/25 mm
Elongation at Break	495%
Shear Strength	> 31 h
Rolling Ball Tack	< 5 cm
Temperature Resistance	-10°C to +50°C
Length	5 m, 25 m, 50 m, 500 m, 1200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	27 November 2019

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V4100



Applications

- Permanent or temporary Carpet laying tape
- Securing of plastic and metal profiles
- General purpose tape
- Industrial splicing and mounting applications
- Good for die-cutting

Benefits

- Excellent adhesion to all different surfaces
- Good conformability on even or uneven surfaces
- Hand tearable
- Adhesive with balanced features for tack, adhesion and cohesion

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 05.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com