


## volzFix V4123 PV2




volzFix V4123 PV2 is a double-sided, differentiated, permanent / removable, self-adhesive tape. It consists of a blue, polyethylene-film carrier and a clear hot-melt, synthetic-rubber adhesive. The product is a perfect exhibition installation tape.

### Nominal Values

<b>Backing</b>	PE Film
<b>Adhesive Type</b>	Synthetic Rubber, different adhesion on each side
<b>Total Thickness</b>	0,130 mm
<b>Color</b>	Blue (11)
<b>Liner</b>	65 g, white, bi-siliconized, Paper
<b>Adhesion to Steel</b>	O: 10,00 N/25 mm, G: 18,00 N/25 mm
<b>Tensile Strength</b>	90,00 N/25 mm
<b>Elongation at Break</b>	> 600%
<b>Shear Strength</b>	O: 4 h, G: 6 h
<b>Rolling Ball Tack</b>	O: 8 cm, G: 6 cm
<b>Temperature Resistance</b>	-10°C to +60°C
<b>Length</b>	25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	27 November 2019

## volzFix V4123 PV2



### Applications

- Perfect exhibition tape

### Benefits

- Hand tearable
- Flexible carrier
- Excellent tack on the open side
- Residue-free on the closed side

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 18.04.2026