

## volzFix V4125 PV2



volzFix V4125 PV2 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a white, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

### Nominal Values

<b>Backing</b>	BOPP Film, Clear
<b>Backing Thickness</b>	0,025 mm
<b>Adhesive Type</b>	Synthetic Rubber, White
<b>Total Thickness</b>	0,085 mm
<b>Color</b>	White (08)
<b>Liner</b>	65 g, white, bi-siliconized, Paper
<b>Adhesion to Steel</b>	18,00 N/25 mm
<b>Tensile Strength</b>	104,00 N/25 mm
<b>Elongation at Break</b>	> 145%
<b>Shear Strength</b>	> 51 h
<b>Rolling Ball Tack</b>	< 2 cm
<b>Temperature Resistance</b>	-10°C to +60°C
<b>Length</b>	25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	05 March 2021

## volzFix V4125 PV2



### Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

### Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 31.07.2025