

## **Technical Product Data Sheet**

### volzFix V4125



volzFix V4125 is a double-sided, self-adhesive tape produced of a clear BOPP-film carrier and a white, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

#### **Nominal Values**

**Backing** BOPP Film, Clear

**Adhesive Type** Synthetic Rubber, plasticizer free, White

**Total Thickness** 0,085 mm

> Liner 65 g, brown, siliconized Paper

**Adhesion to Steel** 18,00 N/25 mm

**Tensile Strength** 104,00 N/25 mm

**Elongation at Break** > 145%

> **Shear Strength** > 51 h

**Rolling Ball Tack** < 2 cm

**Temperature Resistance** -10°C to +60°C

> Length 25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 27 November 2019













DE-79227 Schallstadt



# **Technical Product Data Sheet**

### volzFix V4125



### **Applications**

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

### **Benefits**


- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.11.2025













DE-79227 Schallstadt