

volzFix V4133



volzFix V4133 is a double-sided, PET film with a modified solvent acrylic adhesive that has a different adhesive strength on each side. The permanent side has very good adhesion to paper and high energy plastic materials. The adhesive on the removable side has weak adhesion, yet strong enough to hold onto various surfaces temporarily, e.g. glass, ABS, PVC, etc.; and leaves no residue upon peeling. volzFix V4133 has very good durability, which is resistant to UV and temperature changes.

Nominal Values



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com Fax: +49 (0)7664 50500-50 www.volztapes.com











volzFix V4133



Applications

- Applications for posters/ very light objects to be fixed on notice board, window displays other smooth surfaces temporarly
- Applications where repeat/ temporary fixation is required.

Benefits

- Excellent initial tack and aging resistance
- Removable side is residue free
- Excellent adhesion to even surfaces
- Good adhesion to rough surfaces
- Good surface conformity and holding power
- Very good durability, which is resistant to UV and temperature changes

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 09.08.2025



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Phone: +49 (0)7664 50500-0 info@volztapes.com +49 (0)7664 50500-50 www.volztapes.com









