

## **Technical Product Data Sheet**

### volzFix V4140



volzFix V4140 is a double-sided, self-adhesive tape produced of a clea, r BOPP-film carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

#### **Nominal Values**

**Backing** BOPP Film, Clear

**Adhesive Type** Synthetic Rubber, plasticizer free, Clear

**Total Thickness** 0,095 mm

Color Clear (00)

**Liner** 65 g, brown, siliconized Paper

Adhesion to Steel 20,00 N/25 mm

**Tensile Strength** 105,00 N/25 mm

**Elongation at Break** > 150%

**Shear Strength** > 27 h

Rolling Ball Tack < 4 cm

**Temperature Resistance** -10°C to +60°C

**Length** 25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request

**Width** 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 18 February 2022





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











# **Technical Product Data Sheet**

### volzFix V4140



### **Applications**

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

### **Benefits**

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 26.11.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









DE-79227 Schallstadt