

## **Technical Product Data Sheet**

### volzFix V4140



volzFix V4140 is a double-sided, self-adhesive tape produced of a clea, r BOPP-film carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

### **Nominal Values**

**Backing** BOPP Film, Clear

**Adhesive Type** Synthetic Rubber, plasticizer free, Clear

**Total Thickness** 0,095 mm

> Color Clear (00)

Liner 65 g, brown, siliconized Paper

**Adhesion to Steel** 20,00 N/25 mm

**Tensile Strength** 105,00 N/25 mm

**Elongation at Break** > 150%

> **Shear Strength** > 27 h

**Rolling Ball Tack** < 4 cm

**Temperature Resistance** -10°C to +60°C

> Length 25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 18 February 2022





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











# **Technical Product Data Sheet**

### volzFix V4140



### **Applications**

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

#### **Benefits**

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

#### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 09.08.2025













DE-79227 Schallstadt