

volzFix V4142 PV1



volzFix V4142 PV1 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a white, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

Nominal Values

Manufacturer	VOLZ®
Backing	BOPP Film, Clear (00)
Backing Thickness	0,025 mm
Adhesive Type	Synthetic Rubber, White
Total Thickness	0,095 mm
Color	White (08)
Liner	65 g, yellow, bi-siliconized, Paper
Adhesion to Steel	> 22,50 N/25 mm
Tensile Strength	105,00 N/25 mm
Elongation at Break	> 150%
Shear Strength	> 27 h
Rolling Ball Tack	> 5 cm
Temperature Resistance	-10°C to +50°C
Length	25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	08 March 2021

volzFix V4142 PV1



Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 24.11.2024