

Technical Product Data Sheet

volzFix V4142 PV1



volzFix V4142 PV1 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a white, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

Nominal Values

Backing BOPP Film, Clear

Backing Thickness 0,025 mm

> **Adhesive Type** Synthetic Rubber, White

Total Thickness 0,095 mm

> Color White (08)

Liner 65 g, yellow, bi-siliconized, Paper

Adhesion to Steel > 22,50 N/25 mm

Tensile Strength 105,00 N/25 mm

Elongation at Break > 150%

> **Shear Strength** > 27 h

Rolling Ball Tack > 5 cm

Temperature Resistance -10°C to +50°C

> Length 25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 08 March 2021





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









Technical Product Data Sheet

volzFix V4142 PV1



Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 12.12.2025





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









DE-79227 Schallstadt