

Technical Product Data Sheet

volzFix V4143 PV1



volzFix V4143 PV1 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

Nominal Values

Backing BOPP Film, Clear

Backing Thickness 0,025 mm

> **Adhesive Type** Synthetic Rubber, Clear

Total Thickness 0,085 mm

> Color Clear (00)

Liner 65 g, yellow, bi-siliconized, Paper

Adhesion to Steel 18,00 N/25 mm

Tensile Strength 104,00 N/25 mm

Elongation at Break > 145%

> **Shear Strength** > 51 h

Rolling Ball Tack < 2 cm

Temperature Resistance -10°C to +60°C

> Length 25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 09 March 2021















DE-79227 Schallstadt



Technical Product Data Sheet

volzFix V4143 PV1



Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

Benefits


- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 09.08.2025













DE-79227 Schallstadt