

volzFix V4143 PV1



volzFix V4143 PV1 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

Nominal Values

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------|
| Manufacturer | VOLZ® |
| Backing | BOPP Film, Clear (00) |
| Backing Thickness | 0,025 mm |
| Adhesive Type | Synthetic Rubber, Clear |
| Total Thickness | 0,085 mm |
| Color | Clear (00) |
| Liner | 65 g, yellow, bi-siliconized, Paper |
| Adhesion to Steel | 18,00 N/25 mm |
| Tensile Strength | 104,00 N/25 mm |
| Elongation at Break | > 145% |
| Shear Strength | > 51 h |
| Rolling Ball Tack | < 2 cm |
| Temperature Resistance | -10°C to +60°C |
| Length | 25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 09 March 2021 |

volzFix V4143 PV1



Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.11.2024