

volzFix V4143



volzFix V4143 is a double-sided, self-adhesive tape produced of a clear, BOPP-film carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is perfect for carpet laying or bonding of metal and plastics where no high temperatures is needed. The product also has a very high tack.

Nominal Values

Backing	BOPP Film, Clear
Backing Thickness	0,025 mm
Adhesive Type	Synthetic Rubber, Clear
Total Thickness	0,085 mm
Color	Clear (00)
Liner	65 g, brown, bi-siliconized, Paper
Adhesion to Steel	18,00 N/25 mm
Tensile Strength	104,00 N/25 mm
Elongation at Break	> 145%
Shear Strength	> 51 h
Rolling Ball Tack	< 2 cm
Temperature Resistance	-10°C to +60°C
Length	25 m, 50 m, 100 m, 1000 m, 2700 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	27 November 2019

volzFix V4143



Applications

- General purpose tape
- Bonding of foils, cardboards, posters and more
- Carpet laying tape

Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 18.06.2026