

## volzFix V4144 PV1



volzFix V4144 PV1 is a double-sided adhesive tape with a transparent biaxially oriented polypropylene film as internal carrier, a synthetic rubber based adhesive system and a yellow two side siliconized liner. The product is suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing, etc.

### Nominal Values

<b>Backing</b>	BOPP Film, Clear
<b>Backing Thickness</b>	0,060 mm, (± 5%)
<b>Adhesive Type</b>	White, Synthetic Rubber
<b>Total Thickness</b>	0,130 mm, (± 5%)
<b>Color</b>	White (08)
<b>Liner</b>	80 g, (± 10%), Yellow, bi-siliconized, Paper
<b>Adhesion to Steel</b>	25,00 N/25 mm, (± 10%)
<b>Tensile Strength</b>	105,00 N/25 mm, (± 10%)
<b>Elongation at Break</b>	150%, (± 8%)
<b>Shear Strength</b>	17,6 h bei +50°C, (± 10%)
<b>Rolling Ball Tack</b>	4,5 cm, (± 5%)
<b>Temperature Resistance</b>	-10°C to +50°C
<b>Length</b>	5 m, 25 m, 50 m, 500 m, 2600 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	30 October 2020

## volzFix V4144 PV1



### Applications

- Suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing
- Suitable for application in paper and leather surfaces

### Benefits

- Excellent adhesion to all surfaces
- Good adaptability on different surfaces and shapes

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 20.08.2025