volzFix V4144 PV1



volzFix V4144 PV1 is a double-sided adhesive tape with a transparent biaxially oriented polypropylene film as internal carrier, a synthetic rubber based adhesive system and a yellow two side siliconized liner. The product is suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing, etc.

Nominal Values

Backing	BOPP Film, Clear
Backing Thickness	0,060 mm, (± 5%)
Adhesive Type	White, Synthetic Rubber
Total Thickness	0,130 mm, (± 5%)
Color	White (08)
Liner	80 g, (± 10%), Yellow, bi-siliconized, Paper
Adhesion to Steel	25,00 N/25 mm, (± 10%)
Tensile Strength	105,00 N/25 mm, (± 10%)
Elongation at Break	150%, (± 8%)
Shear Strength	17,6 h bei +50°C, (± 10%)
Rolling Ball Tack	4,5 cm, (± 5%)
Temperature Resistance	-10°C to +50°C
Length	5 m, 25 m, 50 m, 500 m, 2600 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	30 October 2020

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V4144 PV1



Applications

- Suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing
- Suitable for application in paper and leather surfaces

Benefits

- Excellent adhesion to all surfaces
- Good adaptability on different surfaces and shapes

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com