

volzFix V4145 PV1



volzFix V4145 PV1 is a double-sided, adhesive-tape with a transparent, biaxially-oriented, polypropylene-film internal carrier, a synthetic-rubber adhesive, and a yellow, two-sided siliconized liner. The product is suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet laying, etc.

Nominal Values

| | |
|-------------------------------|---|
| Backing | BOPP Film, Clear |
| Backing Thickness | 0,060 mm |
| Adhesive Type | Synthetic Rubber, White |
| Total Thickness | 0,120 mm |
| Color | White (08) |
| Liner | 70 gr., yellow, siliconized Paper |
| Adhesion to Steel | > 20,00 N/25 mm |
| Tensile Strength | > 105,00 N/25 mm |
| Elongation at Break | > 150% |
| Shear Strength | > 10 h |
| Rolling Ball Tack | < 8 cm |
| Temperature Resistance | -10°C to +50°C |
| Length | 25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 23 July 2020 |

volzFix V4145 PV1



Applications

- Suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing
- Suitable for application in paper and leather surfaces

Benefits

- Excellent adhesion to all surfaces
- Good adaptability on different surfaces and shapes

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.06.2026