

## volzFix V4145 PV1



volzFix V4145 PV1 is a double-sided, adhesive-tape with a transparent, biaxially-oriented, polypropylene-film internal carrier, a synthetic-rubber adhesive, and a yellow, two-sided siliconized liner. The product is suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet laying, etc.

### Nominal Values

<b>Backing</b>	BOPP Film, Clear
<b>Backing Thickness</b>	0,060 mm
<b>Adhesive Type</b>	Synthetic Rubber, White
<b>Total Thickness</b>	0,120 mm
<b>Color</b>	White (08)
<b>Liner</b>	70 gr., yellow, siliconized Paper
<b>Adhesion to Steel</b>	> 20,00 N/25 mm
<b>Tensile Strength</b>	> 105,00 N/25 mm
<b>Elongation at Break</b>	> 150%
<b>Shear Strength</b>	> 10 h
<b>Rolling Ball Tack</b>	< 8 cm
<b>Temperature Resistance</b>	-10°C to +50°C
<b>Length</b>	25 m, 50 m, 100 m, 1000 m, 2600 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	23 July 2020

## volzFix V4145 PV1



### Applications

- Suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, carpet fixing
- Suitable for application in paper and leather surfaces

### Benefits

- Excellent adhesion to all surfaces
- Good adaptability on different surfaces and shapes

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.09.2025