

## volzFix V4150



volzFix V4150 is a double-sided self-adhesive tape produced of a non woven tissue carrier and a clear hot melt synthetic rubber based adhesive system. The product is perfect for permanent bonding of metal and plastics where no high temperatures are needed. The product has also a very high tack.

### Nominal Values

<b>Backing</b>	Non-Woven
<b>Backing Thickness</b>	0,038 mm, (± 10%)
<b>Adhesive Type</b>	Synthetic Rubber, Clear
<b>Total Thickness</b>	0,110 mm, (± 10%)
<b>Color</b>	Clear (00)
<b>Liner</b>	65 g, (± 10%), brown, bi-siliconized, Paper
<b>Adhesion to Steel</b>	26,25 N/25 mm, (± 10%)
<b>Tensile Strength</b>	16,00 N/25 mm
<b>Elongation at Break</b>	2%
<b>Shear Strength</b>	> 89 h
<b>Rolling Ball Tack</b>	< 5 cm
<b>Temperature Resistance</b>	-20°C to +65°C
<b>Length</b>	25 m, 50 m, 100 m, 1000 m, 2350 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	27 November 2019

## volzFix V4150



### Applications

- General purpose tissue tape
- Suitable for lamination of polyurethane foams as well as for pre-fixing on paper, leather and plastic materials for temporary coupling before definitive fixing
- Suitable for cold flying splices
- Bonding of foils, cardboards, posters and more

### Benefits

- Excellent tack
- Good adhesion
- Good conformability onto different surfaces
- Hand tearable
- Flexible carrier

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 13.06.2026