volzFix V4151



volzFix V4151 is a double-sided, self-adhesive tape produced of a fleece carrier and a clear, hot-melt, synthetic-rubber adhesive. The product is suitable for fastening, laminating and splicing. It is characterized by a good adaptability to different materials and surfaces.

Nominal Values

Backing	Non-Woven
Adhesive Type	Synthetic Rubber, Clear
Total Thickness	0,110 mm
Color	Clear (00)
Liner	60 g, brown, bi-siliconized, Paper
Adhesion to Steel	26,25 N/25 mm
Tensile Strength	15,00 N/25 mm
Elongation at Break	2%
Shear Strength	> 50 h
Rolling Ball Tack	< 3 cm
Temperature Resistance	-10°C to +50°C
Length	25 m, 50 m, 100 m, 1000 m, 2350 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	21 February 2022

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V4151



Applications

- Industrial splicing and mounting applications
- Permanent or temporary bonding of carpets
- Fastening, laminating, splicing

Benefits

- Excellent adhesion on different surfaces
- Good adaptability on different surfaces and shapes
- Easy to remove
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com