volzFix V5130



volzFix V5130 is a double sided self-adhesive tape with a clear polyester carrier and a clear modified solvent acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power even at high and low temperatures.

Nominal Values

Backing	PET Film
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,085 mm
Color	Clear (00)
Liner	80 g, White, bi-siliconized, Paper
Adhesion to Steel	13,00 N/25 mm
Tensile Strength	70,00 N/25 mm
Elongation at Break	90%, (± 10)
Shear Strength	> 30 h
Rolling Ball Tack	□ 4 cm
Temperature Resistance	-30°C to +160°C
Length	5 m, other lengths upon request
Width	50 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	10 December 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V5130



Applications

- Production of corrugated cardboard, paper and treated cardboard and paper
- Mounting and lamination of various insulating and foamed materials, foils and metal plates
- Good for foam lamination

Benefits

- Good tack, very good UV ageing resistance, very good humidity resistance
- Good resistance to chemicals, good softener resistance
- Very aggressive adhesive with high adhesive strength even at high and low temperatures
- Very good converting performance because of a stable PET carrier and reduced adhesive mass flow

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com