volzFix V5133 PV2



volzFixV5133 PV2 is a double-sided adhesive tape consisting of a polyester film backing coated on both sides with a modified acrylic adhesive. It features high resistance to UV radiation, temperature effects, chemicals and solvents, and moisture. In addition, the tape is suitable for permanent bonding to low-energy metal and paint, as well as high-energy plastic surfaces.

Nominal Values

Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	Acrylic
Total Thickness	0,160 mm
Color	Clear (00)
Liner	Red, bi-siliconized, PP Film
Adhesion to Steel	18,00 N/25 mm
Loop Tack	28,00 N/25 mm
Shear Strength	> 400 h
Temperature Resistance	-40°C to +160°C, +180°C (short-term)
Length	50 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1372 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	22 November 2022

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V5133 PV2



Applications

- Self-adhesive finishing of signs, fascia boards, scales, metal and plastic foils
- Fixing aid for e.g., sail production as well as mounting of window bars and moldings

Benefits

- Very high shear strength
- High temperature resistance
- Good permanent adhesion to low energy surfaces
- High initial adhesion
- Excellent permanent adhesion to metal, paint and other high-energy plastic surfaces

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com