

volzFix V52200 PV2

volzFix V52200 PV2 is a PET Scrim reinforced transfer tape with an acrylic based, permanent adhesive. It is suitable for a wide range of applications in the construction, automotive and white goods industries. It is intended for use on clean, dry and flat surfaces, including slightly rough and curved surfaces. With its high initial tack and enduring performance, volzFix V52200 PV2 is ideal for lamination applications with an array of materials including films, felts, and foams.

Nominal Values

Backing	Reinforced Transfer – PET Scrim
Adhesive Type	Acrylic
Color	Clear (00)
Liner	0,08 mm, White PP Film
Adhesion to Steel	28,00 N/25 mm
Static Shear	2 h
Temperature Resistance	-40°C to +120°C
Length	500 m, other lengths upon request
Width	1000 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Additional Info	PET Scrim Weight: 5 g/m ² (±1), Adhesive Weight (inclusive scrim): 200 g/m ² (±5%)
Effective	09 April 2025

volzFix V52200 PV2

Applications

- Various applications in construction, automotive and white goods industries
- Suitable for applications on clean, dry and flat surfaces, including slightly rough and curved surfaces
- Predominantly used for lamination purposes with an array of materials including films, felts, foams
- Difficult bonding applications

Benefits

- High initial tack
- Enduring performance
- Adheres to a wide range of materials

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 19.04.2026