

# volzFix V52200 PV2

volzFix V52200 PV2 is a PET Scrim reinforced transfer tape with an acrylic based, permanent adhesive. It is suitable for a wide range of applications in the construction, automotive and white goods industries. It is intended for use on clean, dry and flat surfaces, including slightly rough and curved surfaces. With its high initial tack and enduring performance, volzFix V52200 PV2 is ideal for lamination applications with an array of materials including films, felts, and foams.

## Nominal Values

<b>Backing</b>	Reinforced Tranfer – PET Scrim
<b>Adhesive Type</b>	Acrylic
<b>Color</b>	Clear (00)
<b>Liner</b>	0,08 mm, White PP Film
<b>Adhesion to Steel</b>	28,00 N/25 mm
<b>Static Shear</b>	2 h
<b>Temperature Resistance</b>	-40°C to +120°C
<b>Length</b>	500 m, other lengths upon request
<b>Width</b>	1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Additional Info</b>	PET Scrim Weight: 5 g/m <sup>2</sup> (±1), Adhesive Weight (inclusive scrim): 200 g/m <sup>2</sup> (±5%)
<b>Effective</b>	09 April 2025

# volzFix V52200 PV2

## Applications

- Various applications in construction, automotive and white goods industries
- Suitable for applications on clean, dry and flat surfaces, including slightly rough and curved surfaces
- Predominantly used for lamination purposes with an array of materials including films, felts, foams
- Difficult bonding applications

## Benefits

- High initial tack
- Enduring performance
- Adheres to a wide range of materials

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 18.02.2026