

volzFix V52200

volzFix V52200 is a reinforced transfer-tape with polyester cloth scrim and a modified acrylic adhesive. It is suitable for reinforcing, strapping, and a wide range of applications in the automotive, appliances, insulations, furniture, textile, packaging, and construction industries.

Nominal Values

Backing	PET Cloth Scrim, 4×1 yarn/cm
Adhesive Type	modified, Acrylic
Total Thickness	0,200 mm, (± 2%), (ohne Liner)
Color	Clear (00)
Liner	80 g/m ² , havana glassine, Paper
Adhesion to Steel	27,00 N/25 mm, AFERA 5001
Shear Strength	1,50 h, 25 mm x 25 mm – 23°C (Edelstahl)
Temperature Resistance	-40°C to +100°C (long-term), -40°C to +120°C (short-term)
Length	500 m, other lengths upon request
Width	1000 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Additional Info	Adhesive weight: 200 (±2) g/m ² , RoHS compliant (2011/65/EU, 2015/863)
Effective	27 November 2023

volzFix V52200

Applications

- Reinforcing
- Strapping
- Challenging bonding applications

Benefits

- Adheres to a wide range of materials
- High adhesive strength

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 28.05.2026