

volzFix V5240

Nominal Values

| | |
|-------------------------------|---|
| Backing | PET Cloth Scrim, 4×1 yarn/cm |
| Adhesive Type | modified, Acrylic |
| Total Thickness | 0,040 mm, (± 2%), (ohne Liner) |
| Color | Clear (00) |
| Liner | 80 g/m ² , havana glassine, Paper |
| Adhesion to Steel | 13,00 N/25 mm, AFERA 5001 |
| Shear Strength | 25 Min., 25 mm x 25 mm – 23°C (Edelstahl) |
| Temperature Resistance | -40°C to +100°C (long-term), -40°C to +120°C (short-term) |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Additional Info | Adhesive weight: 40 (±2) g/m ² , RoHS compliant (2011/65/EU, 2015/863) |
| Effective | 27 November 2023 |

volzFix V5240

Applications

- Reinforcing
- Strapping
- Challenging bonding applications

Benefits

- Adheres to a wide range of materials
- High adhesive strength

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.04.2026