

volzFix V5263 PV1



volzFix5263 PV1 is a transfer adhesive tape consisting of a transparent acrylate adhesive which has an excellent resistance to UV radiation, temperature stress, chemicals, and solvents as well as moisture. The highly shear resistant transfer adhesive features excellent permanent adhesion to metal, paint, and high energy plastic surfaces. The transfer tape is certified according to UL 969

Nominal Values

Backing	Transfer
Adhesive Type	Acrylic
Total Thickness	0,060 mm
Color	Clear (00)
Liner	100 g/m ² , brown, bi-siliconized, PE Paper
Adhesion to Steel	15,00 N/25 mm
Shear Strength	> 1000 h
Temperature Resistance	-40°C to +170°C, +200°C (short-term)
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 100 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	10 August 2021

volzFix V5263 PV1



Applications

- Industrial/commercial bonding of smooth or slightly porous substrates
- Self-adhesive finishing of all types of signs, decorations, front panels and displays where very high shear and adhesion strength as well as temperature resistance are required

Benefits

- Highly resistant to UV radiation, temperature stress, chemicals and solvents, and moisture
- Excellent permanent adhesion to metal, paint and high-energy plastic surfaces

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.12.2025