volzFix V5263



volzFix V5263 is a modified acrylic adhesive coated onto an avana siliconized Paper release liner. Designed for lamination and mounting various materials as fabrics, papers, foams, plastic films, foils and cardboard.

Nominal Values

Backing	Transfer
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,050 mm
Color	Clear (00)
Liner	90 g, brown, bi-siliconized, Paper
Adhesion to Steel	6,25 N/25 mm
Shear Strength	≥ 168 h
Rolling Ball Tack	< 10 cm
Temperature Resistance	-30°C to +110°C, +140°C (short-term)
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 6 months.
Effective	25 February 2022

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V5263



Applications

- Paper and plastic industry, flying splices, core starting, end-tabbing, packaging, etc.
- Lamination of fabrics and foams, mounting of displays, photos, posters, leaflets, etc.

Benefits

- Good tack and adhesion
- Good shear strength and ageing resistance
- Acid free

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com