

volzFix V5265-PE



volzFix V5265 PE is a 125 micron, modified acrylic adhesive wound on a brown siliconized paper release liner. Designed for mounting various materials as fabrics, paper, plastic films, metal foils, cardboard, glass, etc. It has a very high tack and adhesion, with good shear strength and ageing resistance.

Nominal Values

| | |
|-------------------------------|---|
| Backing | Transfer |
| Adhesive Type | modified, Solvent Acrylic |
| Total Thickness | 0,125 mm |
| Color | Clear (00) |
| Liner | brown, bi-siliconized, Paper |
| Adhesion to Steel | 22,50 N/25 mm |
| Shear Strength | 168 h |
| Rolling Ball Tack | < 10 cm |
| Temperature Resistance | -30°C to +110°C, +140°C (short-term) |
| Length | 50 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 17 October 2025 |

volzFix V5265-PE



Applications

- Paper and plastic industry, flying splices, core starting, end-tapping, packaging, etc.
- Laminations of fabrics and foam, mounting of displays, photo, posters, leaflets, etc.

Benefits

- Very high tack and adhesion
- Good shear strength and ageing resistance
- Acid free

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.05.2026