

## volzFix V5265-PE



volzFix V5265 PE is a 125 micron, modified acrylic adhesive wound on a brown siliconized paper release liner. Designed for mounting various materials as fabrics, paper, plastic films, metal foils, cardboard, glass, etc. It has a very high tack and adhesion, with good shear strength and ageing resistance.

### Nominal Values

<b>Backing</b>	Transfer
<b>Adhesive Type</b>	modified, Solvent Acrylic
<b>Total Thickness</b>	0,125 mm
<b>Color</b>	Clear (00)
<b>Liner</b>	brown, bi-siliconized, Paper
<b>Adhesion to Steel</b>	22,50 N/25 mm
<b>Shear Strength</b>	168 h
<b>Rolling Ball Tack</b>	< 10 cm
<b>Temperature Resistance</b>	-30°C to +110°C, +140°C (short-term)
<b>Length</b>	50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	17 October 2025

## volzFix V5265-PE



### Applications

- Paper and plastic industry, flying splices, core starting, end-tapping, packaging, etc.
- Laminations of fabrics and foam, mounting of displays, photo, posters, leaflets, etc.

### Benefits

- Very high tack and adhesion
- Good shear strength and ageing resistance
- Acid free

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.04.2026