

volzFix V5265



volzFix V5265 is a high-mass, transfer tape with a clear, solvent-acrylic adhesive reinforced with glass fiber. It has a very aggressive adhesive with good adhesion, tack and cohesion. manufactured on a 1 inch core and reverse wound for ATG systems.

Nominal Values

Backing	Transfer
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,120 mm
Color	Clear (00)
Liner	90 g, brown, bi-siliconized, Paper
Adhesion to Steel	22,50 N/25 mm
Shear Strength	≥ 168 h
Rolling Ball Tack	< 10 cm
Temperature Resistance	-30°C to +110°C, +145°C (short-term)
Length	16,5 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	25 February 2022

volzFix V5265



Applications

- Mounting of pictures
- Assembling inside of boxes, skin pack, fixing labels on non-stick cookware. Lamination of different materials together.

Benefits

- Reinforced adhesive
- Good tack, good cohesion and good adhesion
- Reverse wounded for the ATG System

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 01.09.2025