

volzFix V5408 PV2

volzFix V5408 PV2 is a double-sided, non-woven tape with a modified solvent acrylic adhesive. With good adhesion, it is a general purpose tape, adhering light-weight objects to a variety of surfaces.

Nominal Values

Backing	Non-Woven
Backing Thickness	0,035 mm
Adhesive Type	Modified Solvent Acrylic
Total Thickness	0,080 mm (± 10%)
Color	Clear (00)
Liner	95 gr., white, PE Paper
Adhesion to Steel	12,50 N/25 mm
Shear Strength	≥ 1 h
Temperature Resistance	-20°C to +60°C
Length	50 m, 100 m, 200 m, 1000 m, other lengths upon request
Width	15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	24 February 2026

volzFix V5408 PV2

Applications

- General adhesion of light weight objects
- Applicable to various surfaces

Benefits

- Good Adhesion
- Applicable to a variety of surfaces

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 23°C to 28°C, with a relative humidity of 50%. When using an adhesive tape stored below 23°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.06.2026