

## volzFix V5408 PV2

volzFix V5408 PV2 is a double-sided, non-woven tape with a modified solvent acrylic adhesive. With good adhesion, it is a general purpose tape, adhering light-weight objects to a variety of surfaces.

### Nominal Values

<b>Backing</b>	Non-Woven
<b>Backing Thickness</b>	0,035 mm
<b>Adhesive Type</b>	Modified Solvent Acrylic
<b>Total Thickness</b>	0,080 mm (± 10%)
<b>Color</b>	Clear (00)
<b>Liner</b>	95 gr., white, PE Paper
<b>Adhesion to Steel</b>	12,50 N/25 mm
<b>Shear Strength</b>	≥ 1 h
<b>Temperature Resistance</b>	-20°C to +60°C
<b>Length</b>	50 m, 100 m, 200 m, 1000 m, other lengths upon request
<b>Width</b>	15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1240 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	24 February 2026

## volzFix V5408 PV2

### Applications

- General adhesion of light weight objects
- Applicable to various surfaces

### Benefits

- Good Adhesion
- Applicable to a variety of surfaces

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 23°C to 28°C, with a relative humidity of 50%. When using an adhesive tape stored below 23°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 30.04.2026