

volzFix V9017



volzFix V9017 is a double-sided adhesive tape made of a transparent PET carrier and a modified acrylic adhesive with different adhesive strength. The adhesive on the open side of the tape is characterized by high temperature resistance, high tack and insensitivity to moisture. The covered adhesive can be easily removed from many material surfaces again without leaving any residues

Nominal Values

Manufacturer	VOLZ®
Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	modified, Acrylic, different adhesion on each side, open side(O): permanent sticking, closed side(G): removable
Total Thickness	0,100 mm
Color	Clear (00)
Liner	90 g/m ² , brown, bi-siliconized, Paper
Adhesion to Steel	O: 16,00 N/25 mm, G: 1,00 N/25 mm
Loop Tack	10,00 N/25 mm
Shear Strength	O: >48 h, G: > 500 h
Temperature Resistance	-40°C to +120°C
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	10 January 2023

volzFix V9017



Applications

- Suitable as a self-adhesive medium for different materials
- Ideal for situations where easy and residueless removal is required

Benefits

- Covered side easily removable
- Open side permanently adhesive, even on low-energy surfaces, rough surfaces and foams

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.11.2024