

## volzFix V9062 PV1



volzFixV9062 PV1 is a double-sided adhesive tape consisting of a paper fleece backing coated on both sides with a modified acrylate adhesive. The adhesive is characterized by high temperature and aging resistance, as well as high adhesive strength with extensive plasticizer resistance

### Nominal Values

|                               |   |
|-------------------------------|---|
| <b>Backing</b>                | Non-Woven   |
| <b>Adhesive Type</b>          | modified, Acrylic   |
| <b>Total Thickness</b>        | 0,160 mm  |
| <b>Color</b>                  | Clear (00)  |
| <b>Liner</b>                  | 90 g, yellow, bi-siliconized, Paper   |
| <b>Adhesion to Steel</b>      | 23,00 N/25 mm   |
| <b>Loop Tack</b>              | 26,00 N/25 mm   |
| <b>Shear Strength</b>         | ≥ 72 h  |
| <b>Temperature Resistance</b> | -40°C to +140°C   |
| <b>Length</b>                 | 50 m, other lengths upon request  |
| <b>Width</b>                  | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1550 mm, other widths upon request |
| <b>Storage Life</b>           | The material can be stored at room temperature for at least 12 months.                          |
| <b>Effective</b>              | 26 February 2026  |

## volzFix V9062 PV1



### Applications

- Suitable for the adhesion of cellular rubber
- Appropriate for the adhesion of textiles, wood, open-pore and impregnated foams, cellular polyethylene, soft PVC and other rough, open surfaces

### Benefits

- Good resistance to temperature variations, solvents, humidity
- Largely plasticizer resistant
- High peel adhesion

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.06.2026