volzFix V9062 PV1



volzFixV9062 PV1 is a double-sided adhesive tape consisting of a paper fleece backing coated on both sides with a modified acrylate adhesive. The adhesive is characterized by high temperature and aging resistance, as well as high adhesive strength with extensive plasticizer resistance

Nominal Values

Backing	Non-Woven
Adhesive Type	modified, Acrylic
Total Thickness	0,160 mm
Color	Clear (00)
Liner	90 g, yellow, bi-siliconized, Paper
Adhesion to Steel	23,00 N/25 mm
Loop Tack	26,00 N/25 mm
Shear Strength	≥ 72 h
Temperature Resistance	-40°C to +140°C
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1550 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	26 February 2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzFix V9062 PV1



Applications

- Suitable for the adhesion of cellular rubber
- Appropriate for the adhesion of textiles, wood, open-pore and impregnated foams, cellular polyethylene, soft PVC and other rough, open surfaces

Benefits

- Good resistance to temperature variations, solvents, humidity
- Largely plasticizer resistant
- High peel adhesion

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com