

volzFix V9062 PV1



volzFixV9062 PV1 is a double-sided adhesive tape consisting of a paper fleece backing coated on both sides with a modified acrylate adhesive. The adhesive is characterized by high temperature and aging resistance, as well as high adhesive strength with extensive plasticizer resistance

Nominal Values

Backing	Non-Woven
Adhesive Type	modified, Acrylic
Total Thickness	0,160 mm
Color	Clear (00)
Liner	90 g, yellow, bi-siliconized, Paper
Adhesion to Steel	23,00 N/25 mm
Loop Tack	26,00 N/25 mm
Shear Strength	≥ 72 h
Temperature Resistance	-40°C to +140°C
Length	50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1550 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	26 February 2026

volzFix V9062 PV1



Applications

- Suitable for the adhesion of cellular rubber
- Appropriate for the adhesion of textiles, wood, open-pore and impregnated foams, cellular polyethylene, soft PVC and other rough, open surfaces

Benefits

- Good resistance to temperature variations, solvents, humidity
- Largely plasticizer resistant
- High peel adhesion

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.06.2026