

volzFix V9067



volzFix 9067 is a double-sided adhesive tape with polyester-film carrier and a modified-solvent acrylic adhesive. Suitable for applications where a thin and highly transparent tape is required.

Nominal Values

Backing	PET Film
Backing Thickness	0,012 mm
Adhesive Type	modified, Solvent Acrylic
Total Thickness	0,160 mm
Color	Clear (00)
Liner	90 g/m ² , brown, siliconized Paper
Adhesion to Steel	18,00 N/25 mm
Loop Tack	28,00 N/25 mm
Shear Strength	> 400 h
Temperature Resistance	-40°C to +160°C, +180°C (short-term)
Length	50 m, 500 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	11 August 2021

volzFix V9067



Applications

- Widely used in the membrane switch and electrical industry (e.g. smart phones)
- Modular construction
- Production of corrugated cardboard and paper, and treated cardboard, paper foils, and metal plates
- Mounting and lamination of various insulating and foamed materials
- Applications where high transparency is required
- Good for foam lamination

Benefits

- Good tack, very good UV ageing resistance, very good humidity resistance
- Good resistance to chemicals, good softener resistance
- Very aggressive adhesive with high adhesive strength even at high and low temperatures
- Very good converting performance because of a stable PET carrier and reduced adhesive mass flow

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 10.04.2025