

Technical Product Data Sheet

volzMasking 3016U

volzMasking 3016U is a masking tape suitable for curing at 80°C (1 hour) in automotive repair shops, especially car body shops.

Nominal Values

Backing Saturated Crepe Paper

Backing Thickness 0,090 mm

> **Adhesive Type** Natural rubber and Hydrocarbon Resins

Total Thickness 0,132 mm

> Color Ivory (00), other colors upon request

Adhesion to Steel 6,75 N/25 mm

Tensile Strength 85,00 N/25 mm

Elongation at Break 10%

Temperature Resistance +80°C (1 h)

> Length 50 m, other lengths upon request


Width 19 mm, 25 mm, 50 mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 24 March 2025







Phone: +49 (0)7664 50500-0 +49 (0)7664 50500-50 www.volztapes.com Fax:

info@volztapes.com



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of







DE-79227 Schallstadt



Technical Product Data Sheet

volzMasking 3016U

Applications

Masking tape for the automotive industry

Benefits

- Excellent adhesion to all surfaces
- Easy application on curved profiles and irregular surfaces
- Easy removal without adhesive residue
- Heat resistant up to 80°C (1 hour)
- Compatible with solvent-based and most water-based paints


Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.11.2025







DE-79227 Schallstadt

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the









standard processing guidelines for adhesive tapes, which we will gladly send you upon request.